

Order number: 237500008

Open text field 1:



- Due to the already glued heating mat, this installation step is omitted

CAS 120/W:

- Consists of reflector and feed system mounting
- Exchangeable multi-feed adaptor plate included
- Reflector in proven powder coated aluminium design
- 10 year corrosion durability guarantee in accordance with KATHREIN guarantee terms
- Powder coated galvanised sheet steel feed system mounting and mirror rear construction
- Patented multi-feed adaptor plate tilt facility in stable, corrosion resistant die-cast aluminium
- Weatherproof plastic snap-in cable holder for up to eight coaxial cables
- Optimum electrical specification with ultra-compact mechanical dimensions thanks to offset feed and tilting multi-feed adaptor plate for positioning feed systems at the typical side focuses for multi-feed reception
- Two universal feed systems can be mounted on the carrier arm without additional components for reception of 3° to 4° (e.g. ASTRA 19.2°/23.5°) or 6° offset satellites
- At 6° satellite offset, a central feed system can also be installed (three satellites each 3° offset)
- Also required for installation: ZAS 120 azimuth / elevation clamp
- Colour: White

ESO 120 H:

- Good heat distribution due to an optimal fit of the heating mat on the reflector
- Element carrier of aluminium foil, self-adhesive foil strips at the front
- Thermal insulation made of bubble wrap with reflective layer, 4 mm
- Built-in sensor to additionally define the heating temperature via a control
- Operation without control possible
- Operation with the following controls possible: ESO 005, ESO 96 S, ESO 97 S, ESO 97 SL



Hersteller: Kathrein

CAS 120 H

Product information "CAS 120 H"

Sat antenna CAS 120/W **including already mounted flexible special heating mat ESO 120 H** with integrated thermal insulation and PTFE-insulated heating elements

Type: CAS 120 H

Order no.: 2375000008

Consisting of: CAS 120/W + ESO 120 H

Mehr Bilder zu "CAS 120 H"

