



UAS 584/S

Professional Universal Quattro Feeding System

Order no.: 20110022



- Universal quattro feed system (4 outputs) for Kathrein satellite antennas, type CAS 120, CAS 124 and CAS 180
- For reception of satellites in the Ku-band, such as ASTRA, EUTELSAT or TürkSat
- The feed system complies with the ASTRA specification for universal SMATV systems
- Power supply is via coaxial cable
- Multifeed capable due to compact design
- Complete protection of LNB and cable connections in ventilated housing, protection class: IP 54

Status 08/2023

Technische Daten / Technical Data:

Type:	UAS 584/S
Order no:	20110022
Polarization:	4 x (2 x horizontal and 2 x vertical)
Input frequency:	10.7 – 11.7 GHz 11.7 – 12.75 GHz
Reinforcement:	> 50 dB
Output frequency:	950-1950 and 1100-2150 MHz
Oscillator frequency (L.O.):	9.750 and 10.60 GHz
Phase noise (L.O.: 10.60 GHz):	1 kHz: -50 dBc 10 kHz: -75 dBc 100 kHz: -95 dBc
System grade (G/T):	See technical data SAT antenna
Suitable for satellite antenna:	CAS 120 CAS 124 CAS 180
Polarization decoupling:	Type. 30 dB
Current consumption LNB:	Type. 150 mA
Supply voltage LNB:	11,5 – 19,0 V
Output/impedance:	4 x F-Connector/75 Ω
Weight approx:	0,8 kg
Dimensions:	235 x 135 x 44 mm
Packing dimensions:	295 x 185 x 65 mm

Downloads

- [Kathrein SAT Antennen Zubehör – Produkt Übersicht \(Version: 09/2023 - Größe: 10.33 MB\)](#)
- [Kathrein Speisesysteme LNB's – Produkt Übersicht \(Version: 09/2023 - Größe: 749.04 KB\)](#)
- [Kathrein SAT Antennen - Produkt Übersicht \(Version: 09/2023 - Größe: 1.09 MB\)](#)
- [UAS 584/S - Produktdatenblatt \(Version: 04/2023 - Größe: 87.53 KB\)](#)
- [UAS 584/S - Bedienungsanleitung | User Manual \(Version: 1 - Größe: 749.64 KB\)](#)



Produkt Galerie:

