

Order number: 20110020

Open text field 1:



- 5 year guarantee in accordance with KATHREIN guarantee terms
- For reception from satellites in the Ku band, e.g. ASTRA, EUTELSAT or TürkSat
- The feed system complies with the ASTRA specification for universal feed systems
- For communal units with two polarisations and two frequency ranges (2 x low/high band)
- For linear polarisation
- Equipped with quad LNB (four switchable outputs)
- For four connections without additional multi-switch
- Independent horizontal/vertical, low/high band selection from each receiver
- Horizontal/vertical, low/high band switching are carried out by coaxial cable using 14/18 V and 22 kHz
- Power supply via drop cable
- Multi-feed compatible due to compact construction (CAS 60/80/90/120)
- Complete protection of LNB and cable connections in vented housing, protection class: IP 54
- Extendable to up to 16 connections with EXR 15xx multi-switches



Hersteller: Kathrein

UAS 585

Product information "UAS 585"

Universal quad feed system - 10.70-12.75 GHz - 4 switchable outputs (14/18 V, 0/22 kHz) - Current drain: 200 mA - Multi-feed compatible

Type:	UAS 585
Order no.:	20110020
Polarisation:	Switchable
Input frequency:	Switchable
Gain:	> 50 dB
Output frequency:	950-1950/1100-2150 MHz
Oscillator frequency (L.O.):	9,75/10,60 GHz
Phase noise (L.O.: 10.60 GHz):	1 kHz: -50, 10 kHz: -75, 100 kHz: -95 dBc
Figure of merit (G/T):	See offset parabolic antennas dB/K
Suitable for sat antenna:	CAS 60/80/90/120
Polarisation decoupling:	Typ. 25 dB
Current drain LNB:	Typ. 200 mA
Supply voltage LNB:	Switched mode
Output/impedance:	4 x F connector/75 Ω
Weight (approx.):	1.16 kg
Dimensions:	235 x 135 x 44 mm
Packing unit:	295 x 185 x 65 mm

Mehr Bilder zu "UAS 585"

